



Unidos en la tracción  
de su siembra



**Motor:**

Model 9LD626 /air cooled

Manufacturing lombardini 30 hp 4WD

Number of cylinders 2 diesel

Cooling twin air extractor

**Clutch:**

Single dry plate with foot control

**Transmission:**

9-speed: 6 front and 3 reverse

1 before 1.2Km/H

2 before 2.5Km/H

3 before 3.8Km/H

4 before 6.5Km/H

5 before 13.7Km/H

6 before 20.6Km/H

1 reverse 1.6Km/H

2 reverse 3.3Km/H

3 reverse 5Km/H

**Bodywork:**

open hood from its hinges completely for full access to the motor

**brakes:**

the service and parking brakes act mechanically on rear wheels

**weight:**

820 kg in ordinary conditions without subsequent lasters

**differential coupling:**

in both trees, with provision for simultaneous fixation

**operation / impulse:**

4ruedas driving the same diameter

**management:**

central joint power steering

**P.T.O.:**

top position in 2 speeds backwards independent 540-879 RPM or synchronized with all right rotation

speed drive of the profile delasaø 13 / 8

bottom-back position in 2 independent speeds 540 to 879 RPM or synchronized with all speeds trawl counterclockwise rotation

**wheels and tires:**

Wheel number 4 for 7.5 \* 16 ISO wheel diameter

**caution lights:**

battery unit charging parking lights  
light fuel load orientation  
night on the road  
Trailer turn signals

**elevation:**

hydraulic three-point elevation  
jack to lift max weight according to ISO  
paco effort with the hydraulic jack handle  
levantade is a touch up to 1060 kg

