



MASSEY FERGUSON

# اساحبات زراعية | MF7140

تفتخر شركة "ماسي فورمسن" البريطانية بتقديم أحدث منتجاتها في مجال صناعة الجرارات الزراعية العملاقة عبر الموديل (MF7140) ذو القدرة الحصانية العالية (140hp) والملائم لأجواء وظروف العمل القاسي في منطقة الشرق الأوسط وهو النوع المتطور للجرار السابق الشهير والمعروف بـ (MF660) وفيما يلي سرد سريع لأهم مميزات هذا المنتج:

- اسم المنتج / الحجم : جرار زراعي / عملاق
- اسم المصنع / المنشأ : ماسي فورمسن / أيرلندا
- سنة الصنع / الحالة : 2010 / جديد
- القوة الحصانية : 140 حصان
- عدد السننرات : 6 (مع شاحن توربينتي)
- ناقل الحركة : ميكانيكية؛ 12 أمامي / 5 خلفي
- نوع الدفع : ديل اكسل (دفع رباعي)
- سرعة العمود الخلفي : 1000/540 دورة
- قوة الرفع الخلفي : 4700 كغ

- ✓ محرك ديزل حديث بقدرة جبارة بلائم أجواء الشرق الأوسط.
- ✓ ناقل الحركة حديث ومتزامن السرعة.
- ✓ محاور أمامية وخلفية جديدة بالكامل ذات سعة تحمل عالية.
- ✓ منظومة هيدروليكية حديثة ذات جريان عالي التدفق.
- ✓ غطاء محرك حديث من قطعة واحدة يفتح للإعلى.
- ✓ شكل حديث بالكامل مع حجرة قيادة مريحة.
- ✓ قوة إضافية وكفاءة عالية وإنتاجية كبيرة.
- ✓ اقتصادي في استهلاك الوقود.
- ✓ بسيط ومريح في القيادة والاستخدام.
- ✓ قدرة رفع أكبر لملحقات زراعية ثقيلة وضخمة.
- ✓ سهولة الوصول إلى كافة أجزائه لغرض الفحص والصيانة.
- ✓ مدعوم فنياً بالكامل داخل العراق.

NEW

A subsidiary of:

 **AGCO**  
Your Agriculture Company

المسوق الرسمي في العراق:

الشركة العامة للتجهيزات الزراعية

بغداد - الوزيرية

هاتف: 4250843 - 4260211

www.iraqiscas.com



# Specifications

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

Engine Performance		MF 7140	MF 7150	MF 7170	MF 7180
Rated hp @ 2200 rev/min	ISO TR14396	140 (103)	150 (111)	170 (125)	180 (132)
Max. torque @ 1400 rev/min	ISO TR14396	600	600	880	720
<b>Power take-off</b>					
Engine speed @ 540/1000 rev/min	rev/min	2143/2160	2143/2160	2143/2160	2143/2160
Type		Two speed IPTO			
<b>Engine</b>					
Diesel, direct injection		AGCO-SISU POWER			
Type	litre/no. cylinders	620 DS Turbo 6.6/6			
<b>Transmission</b>					
Type		12 forward and 5 reverse, synchromesh			
Gears (4-12 rev/min)		7	7	7	7
<b>Linkage and Hydraulics</b>					
Linkage control		Electronic control of draft, position, Intermix, height/depth, rate of drop, 'quick soil engagement' and Active Transport Control.			
High Flow Load Sensing		●	●	●	●
Max. oil flow at pressure	litre/bar	98/125	138/200	138/200	138/200
Lower links		Cat 2 ball ends			
Maximum oil capacity, at PPK ends	litre	4700	4700	4700	4700
	kg	5500	5500	5500	5500
Spool valves		4	4	4	4
<b>Steering</b>					
Type - Standard		Hydrostatic, full-time, 4-wheel steering column			
<b>Brakes</b>					
Oil-cooled, multi-plate discs, hydraulic actuation					
<b>Operator area</b>					
Cab		ISO mounted, Deluxe seat, air conditioning, front and rear mounted worklights, seven pin trailer connector.			
Platform		ISO mounted, Deluxe seat, safety frame and sun canopy.			
<b>'Standard wheels and tyres'</b>					
Front		16.9-28	16.9-28	16.9-28	16.9-28
Rear		20.8-38	20.8-38	20.8-38	20.8-38
<b>Weights and dimensions (approximate with 'standard' wheels and tyres and ballast, less fuel)</b>					
Weight - Cab/Platform	Kg	7700/7480	8250/8030	9350/9130	9940/9720
<b>Dimensions</b>					
Overall length <sup>1</sup>	m	5070	5070	5070	5070
Maximum height	m	3140	3140	3140	3140
Wheelbase	m	3070	3070	3070	3070
<b>Capacity</b>					
Fuel tank	litre	420	420	420	420

- = Standard      ○ = Not applicable/available  
 ○ = Optional      ○ = ISO TR14396  
 † = Measured to front of weight